

(19) World Intellectual Property
Organization
International Bureau



537740

(43) International Publication Date
25 November 2004 (25.11.2004)

PCT

(10) International Publication Number
WO 2004/101402 A1

(51) International Patent Classification⁷: **B65G 11/20**,
47/46, 47/19

(21) International Application Number:
PCT/IB2004/000689

(22) International Filing Date: 25 February 2004 (25.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA200300729 14 May 2003 (14.05.2003) DK

(71) Applicant (for all designated States except US): F.L.
SMIDTH A/S [DK/DK]; Vigerslev Allé 77, DK-2500
Valby (DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CEDERGAARD,

Niels, Ole [DK/DK]; Hobrovej 4a, DK-9550 Mariager
(DK). FÖNS, Mogens, Juhl [DK/DK]; Glenstrup Sövej
1, DK-8990 Fårup (DK).


(74) Agents: KYLIN, Peter et al.; Hynell Patenttjänst AB, Pa-
tron Carls Väg 2, S-683 40 Hagfors/uddeholm (SE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: DEVICE FOR DIVIDING A STREAM OF PARTICULATE OR PULVERULENT MATERIAL INTO SUBSTREAMS



(57) Abstract: Abstract Described is a device (1) for divid-
ing a stream of particulate or pulverulent material into at least
two substreams, said device comprising a housing (2) with a
substantially vertical inlet duct (3) and two or more outlet
ducts (4, 5, 6, 7) emanating from separate openings, and be-
ing separated by means of partition walls (9) extending radi-
ally relative to the centreline of the inlet duct (3), and a rotor
11 which is located in immediate extension of the inlet duct
(3), with its axis of rotation coinciding with the centreline
(10) of the inlet duct, said rotor (11) having a radially con-
figured surface (11a) for directing the falling material stream
radially outwards into the free space (12) above the outlet
ducts. The device is peculiar in that the radial partition walls
(9) can be adjusted in the circumferential direction. The re-
sult will be a freely variable ratio between an arbitrary num-
ber of outlet substreams.



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*